759.1633-05

CORD EXTENSION
CORD EXTENSION 3x4mm² 5m



* Product image may be indicative

CE

IEC 60079-0 (2017)
IEC 60079-31 (2013)
EN 60079-7 (2015)
EN IEC 60079-7/A1 (2018)
IEC 60079-7/AMD1 (2017)
EN 60079-31 (2014)
EN 60079-1 (2014)
IEC 60079-1 (2014)
EN IEC 60309-2 (2022)
IEC 60079-31 (2022)
EN IEC 60309-1 (2022)
EN IEC 60309-4 (2022)
EN IEC 60079-0 (2018)
IEC 60309-1 (2021)
IEC 60309-2 (2021)
IEC 60309-4 (2021)
IEC 60079-7 (2015)

ATEX directive 2014/34/EU

GENERAL CHARACTERISTICS

Commercial Series	OPTIMA-EX[GD] Series
Synthetical description	CORD EXTENSION

Description

The OPTIMA-EX[GD] Series - II 2GD cord extension is engineered for demanding industrial environments, offering robust performance with a rated current of 16A and a rated voltage of 200-250V. Designed with a protection degree of IP66, it ensures superior resistance to dust and water ingress, making it suitable for harsh conditions. The extension features a 5-meter cable length with a 3x4mm² cable section, providing ample reach and reliable conductivity. This product is meticulously crafted to meet stringent industrial standards, ensuring durability and efficiency in electrical distribution tasks.

TECHNICAL CHARACTERISTICS

Poles	2P+E
Rated current	16A
Hour position	6h
Rated voltage	200-250V
Cable section	3x4mm²

PHYSICAL CHARACTERISTICS

Protection degree IP	IP66
Material	ENGINEERING PLASTIC
Colour	BLACK

DIMENSIONAL CHARACTERISTICS

Cable length	5m

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]
Instruction manual
Instruction manual
Instruction manual
Instruction manual
Instruction manual
Instruction manual